



Industrial Lubricants

Row	Properties	Unit	Result	Test Method		
1	Appearance	-	Homogeneous	-		
2	Density @ 15.6 °C	gr/cm ³	0.8389(+/- 5%)	ISIRI 197	ASTM D1298	
3	Flash Point	°C	49 (+-5%)	ISIRI 19695	ASTM D93	
4	Colour	-	2<3	ISIRI 203	ASTM D1500	
5	Viscosity Kin 40 °C	Mm ² /s	5.069(+/-5%)	ISIRI 340	ASTM D445	
6	Sulfur Total	WT%	0.4091>0.0300	ISIRI 8402	ASTM D4294	
7	Pour Point	°C	-12(+/-5%)	ISIRI 201	ASTM D97	
8	Corrosion 3h@100-c	-	1a	ISIRI 336	ASTM D130	
9	Distillation	I.B.P	°C	152 (+-5%)	ISIRI 6261	ASTM D86
		5%	°C	161(+/-5%)		
		10%	°C	164(+/-5%)		
		20%	°C	170(+/-5%)		
		30%	°C	176(+/-5%)		
		40%	°C	195(+/-5%)		
		50%	°C	374(+/-5%)		
		60%	°C	>390(+/-5%)		
		70%	°C	-		
		80%	°C	-		
		90%	°C	-		
		95%	°C	-		
		Dry Point	°C	-		
		Recovery	Vol%	56(+/-5%)		
		Residue	Vol%	44(+/-5%)		
Loss	Vol%	0				