



Light-Hydrocarbon

Row	Properties	Unit	Limit	Test Method
1	Appearance	-	homogenous	
2	Density @ 15 °C	Kg/m ³	785	ASTM D 1298
3	Distillation:			ASTM D 86
4	I.B.P	°C	152	ASTM D 86
5	10% Evaporated @	°C	160.5	ASTM D 86
6	20% Evaporated @	°C	161.5	ASTM D 86
7	30% Evaporated @	°C	162.5	ASTM D 86
8	40% Evaporated @	°C	164.5	ASTM D 86
9	50% Evaporated @	°C	166.5	ASTM D 86
10	60% Evaporated @	°C	169	ASTM D 86
11	70% Evaporated @	°C	173	ASTM D 86
12	80% Evaporated @	°C	180	ASTM D 86
13	90% Evaporated @	°C	201	ASTM D 86
14	95% Evaporated @	°C	230	ASTM D 86
15	F.B.P	°C	252	ASTM D 86
16	Recovery	ml	99	
17	Residue	ml	0.7	
18	Loss	ml	0.3	
19	Color	-	<0.5	ASTM D 155
20	Flash Point	°C	42	D 56
21	Corrosion-3hrs @ 100 °C	-	1a	ASTM D 130
22	Sulphur Total	Wt%	0.108	ASTM D 1265
23	Mercaptan	p.p.m	60.8	