



## Thinner 20000

Row	Properties	Unit	Limit	Test Method
1	Density @ 15 °C	Kg/m <sup>3</sup>	Report	ASTM D 1298
2	Distillation:			ASTM D 86
3	10% Evaporated @	°C	65 max	ASTM D 86
4	50% Recovered @	°C	115 max	ASTM D 86
5	90% Evaporated @	°C	180 max	ASTM D 86
6	F.B.P	°C	205 max	ASTM D 86
7	Residue	Vol%	2 max	ASTM D 86
8	Loss	Vol%	Report	ASTM D 156
9	Sulphur Total	Wt%	0.1 max	ASTM D 1266
10	Corrosion 3hrs @ 50 °C	-	1a	ASTM D 130
11	Vapor Pressure, Reid@ 37.8 °C	kpa	-	ASTM D 323
12	Gum Content (AIR JET)	Mg/100ml	4 max	ASTM D 381
13	Induction Period@ 100 °C	mins	480 min	ASTM D 525
14	Color (Lovi Bond)	-	Red (1.0 kg/1000m <sup>3</sup> )	IP 17
15	Metallic Lead	g/lit	0.013 max	ASTM D 3341
16	Octane Number (Research)	-	87 min	ASTM D 2699
17	Mercaptan Content	ppm	5 max	ASTM D 3227
18	MTBE	% m/m	report	-
19	Oxygen	Wt%	2.7 max	-