



Thinner A95

Row	Properties	Unit	Result	Test Method		
1	Appearance	-	Homogeneous	-		
2	Density @ 15.6 °C	gr/cm ³	0.7779 (+- 5%)	ISIRI 197	ASTM D1298	
3	Flash Point	°C	Free	ISIRI 19695	ASTM D93	
4	Color	-	1<1.5	ISIRI 203	ASTM D1500	
5	Ron	ppm	95(+5%)	ISIRI	ASTM D	
6	MON	ppm	86(+5%)	ISIRI	ASTM D	
7	AKI	ppm	90(+5%)	ISIRI	ASTM D	
8	Sulfur Total	WT%	0.0066>0.0150	ISIRI 8402	ASTM D4294	
9	Benzene	-	0.26>0.30	ISIRI	ASTM D	
10	Aromatics	-	35<	ISIRI	ASTM D	
11	Olefin	-	0	ISIRI	ASTM D	
12	Methanol	-	1.60>1.70	ISIRI	ASTM D	
13	Ethanol	-	1.60>1.91	ISIRI	ASTM D	
14	Corrosion 3h@100-c	-	1a	ISIRI 336	ASTM D130	
15	Distillation	I.B.P	°C	51 (+-5%)	ISIRI 6261	ASTM D86
		5%	°C	62(+5%)		
		10%	°C	71(+5%)		
		20%	°C	85(+5%)		
		30%	°C	95(+5%)		
		40%	°C	104(+5%)		
		50%	°C	111(+5%)		
		60%	°C	117(+5%)		
		70%	°C	124(+5%)		
		80%	°C	133(+5%)		
		90%	°C	148(+5%)		
		95%	°C	158(+5%)		
		Dry Point	°C	177(+5%)		
		Recovery	Vol%	99.5(+5%)		
		Residue	Vol%	0		
Loss	Vol%	0.5				