



Light Hydrocarbon-2nd End

Row	Properties	Unit	Limit	Test Method
1	Density @ 15 °C	Kg/m ³	782 (+-1)	INSO 197
2	Color	-	+29 (+-2)	INSO 2932
3	Distillation:		-	ASTM D 86
4	I.B.P	°C	158 (+-5)	ASTM D 86
5	5% Evaporated @	°C	163.5 (+-5)	ASTM D 86
6	10% Evaporated @	°C	165.5 (+-4)	ASTM D 86
7	20% Evaporated @	°C	167.5 (+-5)	ASTM D 86
8	30% Evaporated @	°C	168.5 (+-5)	ASTM D 86
9	40% Evaporated @	°C	170.5 (+-5)	ASTM D 86
10	50% Evaporated @	°C	173 (+-5)	ASTM D 86
11	60% Evaporated @	°C	174 (+-5)	ASTM D 86
12	70% Evaporated @	°C	176 (+-5)	ASTM D 86
13	80% Evaporated @	°C	179 (+-5)	ASTM D 86
14	90% Evaporated @	°C	196 (+-6)	ASTM D 86
15	95% Evaporated @	°C	204 (+-6)	ASTM D 86
16	F.B.P	°C	235 (+-7)	ASTM D 86
17	Recovery	ml	99	ASTM D 86
18	Residue	ml	0.9	ASTM D 86
19	Loss	ml	0.1	ASTM D 86
20	Flash Point	°C	56 (+-9)	INSO 198
21	Sulphur Total	Wt%	0.117(+0.01)	INSO 8402
22	Mercptan	ppm	38.6 (+-2)	ASTM D3227
23	Viscosity	-	Not defined	INSO 336