



Light Hydrocarbon-3rd End

Row	Properties	Unit	Limit	Test Method
1	Density @ 15 °C	Kg/m ³	816 (+-1)	INSO 197
2	Color	-	<-16 (+-2)	INSO 2932
3	Distillation:		-	ASTM D 86
4	I.B.P	°C	174 (+-5)	ASTM D 86
5	5% Evaporated @	°C	186 (+-5)	ASTM D 86
6	10% Evaporated @	°C	191 (+-4)	ASTM D 86
7	20% Evaporated @	°C	198 (+-5)	ASTM D 86
8	30% Evaporated @	°C	203 (+-5)	ASTM D 86
9	40% Evaporated @	°C	209 (+-5)	ASTM D 86
10	50% Evaporated @	°C	216 (+-5)	ASTM D 86
11	60% Evaporated @	°C	226.5 (+-5)	ASTM D 86
12	70% Evaporated @	°C	238.5 (+-5)	ASTM D 86
13	80% Evaporated @	°C	260 (+-5)	ASTM D 86
14	90% Evaporated @	°C	299.5 (+-6)	ASTM D 86
15	95% Evaporated @	°C	326 (+-6)	ASTM D 86
16	F.B.P	°C	343 (+-7)	ASTM D 86
17	Recovery	ml	97	ASTM D 86
18	Residue	ml	2.9	ASTM D 86
19	Loss	ml	0.1	ASTM D 86
20	Flash Point	°C	68 (+-9)	INSO 198
21	Sulphur Total	Wt%	0.283(+0.021)	INSO 8402
22	Mercptan	ppm	18.5 (+-1)	ASTM D3227
23	Viscosity	-	Not defined	INSO 336